



Industrial cylinder heated drying ironers

FCI800 - FCIR800 - FCIF800 - FCIFF800



Features

- Large surface contact with linen
- Finger protection and emergency button for more safety
- Automatic cooldown
- Easy to operate microprocessor
- Overdimensioned fan for flexible installation
- Indication of ironing speed and temperature
- Reverse mode possible
- Frequency controlled motor
- Space saving installation against the wall is possible: front return
- Electric, gas or steam heating
- Overheating check system

Options

- Stop pedal

Optional modules*

- Model FCIR 800
Frontal and rear output
- Model FCIF 800
Module R with length folding
- Model FCIFF 800
Ironer with feeding and length folding
- Crossfolder and stacker

* Optional modules can be retrofitted to existing FCI800 ironers



HIGH
OUTPUT



ROBUST
DESIGN



MODULAR
SYSTEM

FCI 3186/800

Roller diameter	807 mm
Useful roller length	3186 mm
Ironing capacity**	195 kg/h
Heating	
Electric	75 kW
Gas*	110 kW
Steaming	190 kg/h
Motor	
Roller motor	0,75 kW
Fan motor	2 x 0,55 (50Hz) / 2 x 0,55 (60Hz) kW
Fan capacity	2 x 1300 m ³ /h
Roller speed	3 - 15 m/min.
Electric connection	3AC/380-415 +N/50,60Hz 3AC/380-415 -N/50,60Hz 3AC/440V/60Hz 3AC/208-240V/50,60Hz
Transport data	
Gross weight	2700 kg (E) / 3000 kg (S) / 2570 kg (G)
Net weight	2610 kg (E) / 2900 kg (S) / 2480 kg (G)
Dimensions HxWxD	1985x4260x1915 mm
Packing dimensions HxWxD	2075x4330x1940 mm

* G20, 20 mbar

** According to ISO 9398-1

