



# INDUSTRIAL TUMBLE-DRYER

## IDR190

9 KG

### FEATURES


- Standard stainless steel drum with large diameter
- Easy-to-use microprocessor (ECT)
- Combination of radial and axial airflow
  - maximal heat transfer
  - low energy consumption
  - short drying time
- Large door opening for easy loading and unloading

### OPTIONS

- Reverse drum
- Full control programmer
- Residual moisture control
  - safe drying of delicate linen
  - humidity detection in %
  - ideal in combination with Softwash®
  - Ideal for dry cleaners, fire departments
  - available on Easy and Full Control
- Stainless steel front



LARGE DOOR  
OPENING



ENERGY  
EFFICIENT



STANDARD  
STAINLESS  
STEEL DRUM

YOUR SMART LAUNDRY PARTNER

# IDR190

DRUM  
 CAPACITY  
 VOLUME (L)  
 DIAMETER (MM)  
 DRYING PERFORMANCE  
 AIRFLOW (M<sup>3</sup>/H)  
 DRYING AVERAGE (L/MIN)  
 GAS HEATING  
 GAS CONNECTION (IN)  
 ELECTRICAL CONNECTION  
 ENERGY (KW)  
 ENERGY (kBTU/H)  
 ELECTRICAL HEATING  
 ELECTRICAL CONNECTION  
 ENERGY (kW)  
 MOTOR  
 FAN (KW)  
 DRIVE (KW)  
 CONNECTION  
 EXHAUST (MM)  
 PROGRAMMER  
 EASY CONTROL  
 - antivandal (ECT)  
 FULL CONTROL  
 DIMENSIONS  
 H X W X D (MM)  
 NET WEIGHT (KG)  
 TRANSPORT DATA  
 PACKED H X W X D (MM)  
 GROSS WEIGHT (KG)

	9
	190
	Ø760
	350
	0,150
	1/2"
	1x 208-240V 50Hz 3x 208-240V 50Hz 3x 380-415V 50Hz 3x 380-415V +N 50Hz 3x 440V 60Hz 3x 480V 50Hz 3x 480V 60Hz
	12,5
	42,7
	3x 208-240V 50Hz 3x 380-415V 50Hz 3x 440V 60Hz 3x 480V 50Hz 3x 480V 60Hz
	6/9/12
	0,37
	0,18
	Ø150
	Standard
	Available
	1465 x 795 x 815
	170
	1570 x 880 x 885
	180

The data concerning dimensions of machines include all extended parts

