



INDUSTRIAL TUMBLE-DRYER

1530 1680
24 KG 35 KG

FEATURES


- Standard stainless steel drum with large diameter
- Easy-to-use microprocessor (Easy Control)
- Radial airflow
 - maximal heat transfer
 - low energy consumption
 - short drying time
- Large door opening (Ø81cm) for easy loading and unloading
- Self cleaning lint screen

OPTIONS

- Reverse drum
- Full Control Programmer (FCT)
- Residual moisture control
 - safe drying of delicate linen
 - humidity detection in %
 - ideal in combination with Softwash®
 - Ideal for dry cleaners, fire departments
 - available on Easy and Full Control
- Stainless steel front



LARGE DOOR
OPENING



ENERGY
EFFICIENT



STANDARD
STAINLESS
STEEL DRUM

	1530	1680
DRUM		
CAPACITY (KG)	24	35
VOLUME (L)	530	680
DIAMETER (MM)	Ø930	Ø930
DRYING PERFORMANCE		
AIRFLOW (M ³ /H)	950	1200
DRYING AVERAGE (L/MIN)	0,384	0,560
GAS HEATING		
GAS CONNECTION (IN)	3/4"	3/4"
ELECTRICAL CONNECTION	3x220-240V 50Hz, 1x220-240V 50Hz, 3x380-415V 50Hz	
ENERGY (KW)	33/39	46/50
ENERGY (kBTU/H)	112,6/133,1	157,9/170,6
ELECTRICAL HEATING		
ELECTRICAL CONNECTION	3x220-240V 60Hz, 3x380-415V 50Hz, 3x480V 60Hz	
ENERGY (kW)	30/36	36/48
STEAM HEATING		
STEAM CONNECTION (NPT)	3/4"	3/4"
ELECTRICAL CONNECTION	1x208V-240V 60Hz (3x380V-415V 50/60Hz)	
STEAM OUTPUT * (kW)	27-36,2	39,3-52,7
STEAM PRESSURE (BAR)	7-10	7-10
MOTOR		
FAN (KW)	0,55	0,55
DRIVE (KW)	0,25	0,25
PROGRAMMER		
EASY CONTROL - antivandal (ECT)	Standard	Standard
FULL CONTROL	Available	Available
CONNECTION		
EXHAUST (MM)	200	
DIMENSIONS		
H X W X D (MM)	1975 x 965 x 1270	1975 x 965 x 1490
NET WEIGHT (KG)	275	305
TRANSPORT DATA		
PACKED H X W X D (MM)	2075 x 1040 x 1320	2075 x 1040 x 1540
GROSS WEIGHT (KG)	300	330

+ = available, The data concerning dimensions of machines include all extended parts

